



SHOWER ELEMENT

Basic Board Classic



Product Information

Basic Board - Unlimited in shape and tile

Unlimited in shape and tile. The Basic Board shower tray substrate element in many versions enables the fast and easy installation of floor-level shower areas. Low construction height, even gradient of approx. 2-3 % to the floor drain and immediate availability for tiling with ceramic or alternative floor coverings, allows fast and trouble-free assembly without thresholds and edges. Custom-made products up to a size of 2500 x 1500 mm provide limitless creative space for individual planning. A fire protection insert is available for public buildings. Various grating designs round off the look of the element. Eccentric and height-adjustable designs give you creative freedom. The extra-flat 'old building renovation' version makes the Basic Board series a real all-rounder!



Your advantages:

- Barrier-free thanks to floor-level installation
- Suitable for wheelchairs, ceramic covering at least 5 x 5 cm
- Firm standing due to a gradient of only approx. 2-31 %
- 22 standard sizes in square, rectangular, pentagonal or quadrant shape
- Optional footstep sound absorption
- Alternatively sealed, absolutely watertight
- Double-sided special coating for the immediate acceptance of ceramic or other floor coverings
- Groove formation for optimum binding to wet screed or for further processing with the BaseTec NF flooring board

- Special sizes and finishes available upon request
- Low element thickness from 30 mm
- Sound insulation in the wall connection area due to factory-fitted standardised insulating tapes
- Factory-fitted sealing tape facilitates sealing in the wall area
- Integrated heat insulation
- Easy, time-saving and clean assembly

Accessories:

Basic Board Rapid

substrate block for height adjustment under the Basic Board, made of extruded polystyrene hard foam, double-sided special coating, with factory-made drain recess. Available to fit all sizes. Material thicknesses: 20, 30, 40, 50, 60, 80 mm

NF flooring board

for connection to the Basic Board; enables the watertight, dry finishing of floors. Easy, fast and safe processing is ensured by being equipped with groove and tongue. Size (L x W x H): $1250 \times 600 \times 40$ mm, with 50 mm footstep sound absorption



Phone +49 (0) 41 44 / 234-0 Fax +49 (0) 41 44 / 234-100

Internet www.stadur.com

